


lichtkram

PRODUKT
eigenschaften

Leuchtentyp: LED Einsatz
Rotation: 0° / 0°
Gewicht: < 0,2 kg

TECHNIKEIGENSCHAFTEN

LED-TYP: COB
Primäranschluß: max. 1400 mA
Leistung: max. 42W



IP20 CE

BASE 111 QR

LICHTFARBEN

warm **WHITE** 2700K CRI(Re) > 80
cosy **WHITE** 3000K CRI(Re) > 80
clear **WHITE** 3500K CRI(Re) > 80
cold **WHITE** 4000K CRI(Re) > 80

red **MEAT** 1750K CRI(Re) > 80
clear **MEAT** 3500K CRI(Re) > 93
gold **BREAD** 2700K CRI(Re) > 97
fresh **VEGGI** 3000K CRI(Re) > 97
deep **WHITE** 3000K CRI(Re) > 93

Code	Licht-Farbe	Klasse	Strom	Winkel	Leistung	Leuchten-Befestigung		Ø	Höhe	Farbe
bei 700mA										
92-1027-30	warm WHITE	2000lm	2045lm	30°	22W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1030-30	cosy WHITE	2000lm	2123lm	30°	22W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1035-30	clear WHITE	2000lm	2168lm	30°	22W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1040-30	cold WHITE	2000lm	2239lm	30°	22W	Leuchtenseitig	-	110,5mm	90mm	schwarz
bei 1050mA										
92-1027-30	warm WHITE	3000lm	3150lm	30°	32W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1030-30	cosy WHITE	3000lm	3270lm	30°	32W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1035-30	clear WHITE	3000lm	3340lm	30°	32W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1040-30	cold WHITE	3000lm	3450lm	30°	32W	Leuchtenseitig	-	110,5mm	90mm	schwarz
bei 1400mA										
92-1027-30	warm WHITE	4000lm	4020lm	30°	42W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1030-30	cosy WHITE	4000lm	4170lm	30°	42W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1035-30	clear WHITE	4000lm	4310lm	30°	42W	Leuchtenseitig	-	110,5mm	90mm	schwarz
92-1040-30	cold WHITE	4000lm	4400lm	30°	42W	Leuchtenseitig	-	110,5mm	90mm	schwarz